



# LAND NAVIGATION





# LAND NAVIGATION



## This Course Consists Of:

- **Compass and Map Basics**
  - **Traveling to a Target**
  - **Topo Map Basics**
  - **Distance Calculations**
  - **Finding Yourself**
- **UTM Coordinate System**
- **Using GPS with a Map**
- **Understanding And Adjusting For Declination**



# LAND NAVIGATION



## Compass Types



**Baseplate**



**Accessory**



**Mirrored – Sighting  
(Preferred)**



**Lensatic**



**Digital**



# LAND NAVIGATION

Copyright 2014-2018 Randall's Adventure & Training®



**Compass Needle – Red Points To Magnetic North**

**Orienting Lines**

**Bearing Index (Read Bearing Here)**

**Orienting Arrow**

**Declination Scale**





# LAND NAVIGATION



## Boxing A Compass





# LAND NAVIGATION

## MAP ORIENTATION

*With Compass  
Adjusted For  
Declination*

1) Adjust dial so "N" is at index line.

2) Align edge of compass with north / south reference line.

3) "Box" compass needle by rotating map.








# LAND NAVIGATION

## Finding An Azimuth With Compass (Map with no grid lines)

### Traveling To a Target On The Map – Step 1



- 1) Draw a line on the map from your starting point to your finish point.
- 2) Orient the map to north.
- 3) Place the compass on the map with the edge of the compass on the line and the bearing arrow pointing at your destination



# LAND NAVIGATION



## Traveling To a Target On The Map – Step 2




**Set Compass Heading** - Turn the dial on the compass until “N” outline arrow boxes the compass needle. Your direction to your target (in degrees) is read at the Index Line on the Dial.





# LAND NAVIGATION

## Traveling To a Target On The Map – Step 3




**Follow Your Heading** - Remove the compass from the map and hold it level, so the Magnetic Needle is free to turn. Turn your body until the red end of the Needle aligns with the Orienting Arrow (boxed) and “N” on the Dial. Using the Direction of Travel Arrow, sight a distant landmark and move to it. Repeat this process until you reach your destination.



# LAND NAVIGATION

## Finding An Azimuth With Compass (Using Grid Lines)

- Draw a line from start to finish.
- Lay the edge of your compass on the line in the direction you are traveling.
- Rotate the compass bezel until the orienting lines align with your North Reference Lines (Make sure that North is pointing to North on the map).
- Pick up your compass, box and travel to the destination.
- Note: The compass shown has already been adjusted for declination.








# LAND NAVIGATION

## Finding An Azimuth With Compass Card (Using Grid Lines)

- Draw a line from start to finish.
- Lay the compass rose on the line so the line crosses through the center of the rose.
- Align N / S line or orienting lines on the compass rose with North Reference Line.
- Read your azimuth on the “Finish” side of the compass rose.
- Note: unless you are using a compass adjusted for declination, you will have to add or subtract the declination value to the value that you acquire from the compass rose.







# LAND NAVIGATION

## Traveling To a Target With A Sighting Compass





# LAND NAVIGATION



## Posting Up


In addition to using natural landmarks as targets for your direction of travel, you can also post up a member of your team as a target.

Another option is the Back Azimuth.



# LAND NAVIGATION

## Back Azimuth



Use a Back Azimuth if you need to verify you are still on your desired direction of travel. This is especially handy when crossing rivers or boxing around objects.

Back Azimuth is 180 degrees from your target azimuth. If your target azimuth is more than 180 degrees, then subtract 180. If it is less than 180, then add 180.





# LAND NAVIGATION



## Boxing Around Objects



Right – Add  
Left - Subtract

- Example direction of original travel is 45 degrees
- Turn 90 degrees to a new azimuth of 135 (count your paces)
- Turn 90 degrees back to the original azimuth of 45 degrees until you are past obstacle
- Turn 90 degrees to a new azimuth of 315 and pace the same amount as the first turn
- Turn 90 degrees back to the original azimuth of 45 degrees and continue on




# LAND NAVIGATION

## LATERAL DRIFT – MISSING YOUR TARGET

If you cannot find your target after walking your azimuth the correct distance, then mark the spot where you think it should be and began a structured search of the area. Make note of your azimuths, pace count and direction changes.

Start your grid small then go larger if you cannot locate the target.

Alternate Methods: Skirmish line as you approach





# LAND NAVIGATION

## Gross Direction Navigation



As obvious from this simple road map, the lost hiker only needs to travel a westerly direction to cross a road and reach civilization.



Always know which general direction crosses a main artery!





# LAND NAVIGATION

## Gross Direction Navigation Aids



Shadow Stick



# LAND NAVIGATION



## Terrain Association Navigation

This is the most widely used method of navigation. The navigator plans his route so that he moves from terrain feature to terrain feature. An automobile driver in a city uses this technique as he moves along a street or series of streets, guiding on intersections or features such as stores, parks or houses. Like the driver, the navigator selects routes or *streets* between key points or *intersections*. These key points can be lakes, mountains, roads or any other terrain feature readily recognized on a map. Before you hike a new area, familiarize yourself with the terrain by studying maps, satellite photos or any other available information.



# LAND NAVIGATION



## Backstops, Handrails & Aiming Off

**BACKSTOPS** are features that typically run perpendicular to your azimuth and located beyond your target point. If you run into your backstop then you know you have traveled too far and missed your target point. Backstops can be rivers, roads, mountains, railroad tracks or any other useable feature.

**HANDRAILS** are features that run parallel to your azimuth. They can be rivers, roads, mountains, or any other useable feature that the navigator can use to continue traveling in the desired direction.


**AIMING OFF** is a process of deliberately adding or subtracting to the desired azimuth so the navigator knows which way to go once they reach a feature (such as a trail or road) that leads to the target.





# LAND NAVIGATION

## Backstops, Handrails & Aiming Off





# LAND NAVIGATION














# TOPO MAP BASICS



# LAND NAVIGATION

## BASICS SYMBOLS


 TRAIL	 OPEN AREAS (CROPLAND PASTURE)
 LIGHT-DUTY ROAD	 WOODED AREAS / VEGETATION
 UNIMPROVED ROAD	 WATER
 RAILROAD	 PURPLE DENOTES NON-SURVEYED MAP REVISIONS
 PRIMARY HIGHWAY	
 SECTION LINE	
 FENCE / FIELD LINE	
<p>■ BUILDINGS (BLACK DENOTES MAN MADE OBJECTS SUCH AS HOUSES, SCHOOLS, CHURCHES, ETC.)</p>	





# LAND NAVIGATION

## Map Scale & Datum



Always set your GPS to the map datum shown on your map!  
Always use the proper scale card for measuring!




# LAND NAVIGATION



## CONTOUR LINES


The closer the contour lines, the steeper the terrain. Check the map for the contour intervals. Contour lines will also have elevation markings.



Example above shows a map with contour intervals of 20 feet.



# LAND NAVIGATION




**Depression**





# LAND NAVIGATION





# LAND NAVIGATION







# LAND NAVIGATION




**Clear Areas / Fields**






# LAND NAVIGATION



**Actual View**



**Topo View**



# LAND NAVIGATION



Actual View



Topo View







# LAND NAVIGATION



## Determining Distance On Map







# LAND NAVIGATION



## DETERMINE DISTANCE TRAVELED BY PACE COUNT

(Not a preferred method. Use checkpoints instead.)

In thick jungle, where landmarks can not always be seen to track your position, pace counting is the best way of measuring distance. Pace counting will allow the navigator to estimate where he is at any given time. To be accurate, the navigator must practice pacing over different types of terrain. First you have to do some calculations. Measure out exactly 100 meters on three types of ground. Flat easy terrain, rougher terrain with some slope and then steep hill terrain. Then on each measured course count your paces (every time your left foot touches the ground or every 2 steps = 1 pace). You will have 3 different pace counts for different types of terrain. Once finished, memorize your pace count for all 3 types.

### Averages

Flat easy terrain	100 meters	65 paces
Rougher terrain with some slope	100 meters	75 paces
Steep hill terrain	100 meters	95 paces

General Rule: You have never traveled as far as you think you have.



# LAND NAVIGATION



## Ranger Pace Count Beads





# LAND NAVIGATION



0  
meters



100  
meters



200  
meters



900  
meters



1000 meters  
(1 kilometer)



1100 meters  
(1km 100m)



5000 meters  
(5 kilometers)







# LAND NAVIGATION



## CONDITIONS THAT AFFECT PACE COUNT

- Slopes – Your pace lengthens on a downslope and shortens on an upgrade.
- Winds – A headwind shortens the pace and a tailwind increases it.
- Surfaces – Sand, gravel, mud, snow and similar surfaces tend to shorten your pace.
- Elements – Falling rain or snow causes the pace to be reduced in length.
- Clothing – Excess clothing or shoes with poor traction affect the pace length.
- Visibility – Poor visibility due to rain, snow, or fog will shorten your pace.



# LAND NAVIGATION



# FINDING YOURSELF



# LAND NAVIGATION

## Baselines



Find two prominent features. Shoot an azimuth to the first one and write it down. Shoot an azimuth to the second one and write it down. You can now travel freely. If you get lost, shoot an azimuth to the first feature and move until you get back on your first azimuth. Shoot an azimuth to your second feature and move until you get back on your second azimuth. You will be back at your starting point once both azimuths are the same as the ones you wrote down.





# LAND NAVIGATION



## RESECTION (without grid lines)

- Orient your map and secure its position. Locate a landmark on the map that you can actually see in the landscape. Take a compass bearing to that landmark by sighting and then rotating compass dial until the needle is boxed. Once you have a bearing, do not move the compass dial. Lay the corner of the compass on the map landmark and rotate the whole compass (not the dial) until the needle is boxed. If done properly the corner of the compass will still be over your landmark. Draw a line along the edge of the compass base.



First identifiable landmark


Draw line on map



# LAND NAVIGATION

## RESECTION - Step 2

- Find a second identifiable landmark on the map and repeat the process from the previous slide. Where the two lines intersect is roughly where you are on the map.
- Finding a third point on the map and repeating the process is called “triangulation” and increases the accuracy of finding your location.





# LAND NAVIGATION



**if you are already on a known location (such as a road, river or mountain ridge) but not sure exactly where you are on this feature, you may only need to shoot one azimuth to determine your exact position on the map**

**INTERSECTION is the reverse of RESECTION. An example of intersection is seeing smoke from a forest fire and determining where the fire is located on a map.**





# LAND NAVIGATION




# PLOTTING COORDINATES



# LAND NAVIGATION



## Map Grids



Always set your GPS to the grid system you are using on the map



# LAND NAVIGATION



## Universal Transverse Mercator (UTM)

**UTM is a rectangular coordinate system based on the latitude and longitude (geographic) coordinate system. With UTM, the earth is divided into 60 zones that allows it to be projected onto maps with minimal distortion. All coordinates are expressed in meters.**


**The UTM grid system is the easiest method of relaying your position to others, finding yourself on a map after getting a location fix with a GPS unit, or navigating to a position on a map using a GPS unit.**






# LAND NAVIGATION

## UTM: 60 Zones and 20 Latitude Bands





# LAND NAVIGATION




UTM Zones



# LAND NAVIGATION

## Universal Transverse Mercator (UTM)







# LAND NAVIGATION



## **Easting:**

Is a 6-digit number to designate the EAST/WEST position in the grid.

The grids are the widest at the equator. Since each grid has a different width, a system was created to measure the distance across a grid starting from the vertical center-line of each grid as opposed to starting from the left or right edge of a grid.

The center line of each grid is called the central meridian. The central meridian is always assigned an easting value of 500,000 meters East. It is expressed as 500,000 mE. As you move west of the central meridian the easting will be a number less than 500,000. As you move to the east of the central meridian the easting will be a number greater than 500,000. An easting of zero will never occur, since a zone is never more than 674,000 meters wide.

## **Northing:**

The second number is called the Northing. It is a 7-digit number that designates how many meters you are north or south of the equator. 0 North begins at the Equator for measurements going north. To avoid negative numbers, the number 10,000,000 has been set at the Equator as a starting point for Northing values south of the Equator.


Northing values count down from this number going south of the Equator.



# LAND NAVIGATION



Copyright 2014-2018 Randall's Adventure & Training®



At the Equator the widest zone is 674,000 meters. So the zone would start at 163,000 meters on the left and end at 837,000 meters on the right at the Equator.  
 $674,000 / 2 = 337,000$ .  $500,000 - 337,000$  equals 163,000



# LAND NAVIGATION



## NORTHING


**The Northing values on the map are the number of meters north or south of the Equator. To avoid negative numbers, Northing values start at 10,000,000 M at the Equator (when going south) and count down.**

**North of the Equator, the numbers on the map are the actual number of meters from the Equator.**






# LAND NAVIGATION



You only have to plot the last 3 numbers. The rest of the coordinate values are provided on the map



# LAND NAVIGATION



Read EASTING First  
Then Read NORTHING



# LAND NAVIGATION

UTM grid reader

1,000 m

4791

4790

4789

9 5

541 6

542 543

Place the corner of the UTM grid reader on the point to be plotted

Each tic = 100 meters on this grid reader


House coordinates = 0541450mE  
4789650mN





# LAND NAVIGATION

## Using GPS with Map/Compass



### Plotting GPS to Map

- 1) Find current location with GPS
- 2) Use scale card to plot current location on the map

### Plotting Map to GPS

- 1) Plot location on map of where you want to go with a scale card
- 2) Enter plotted coordinates into the GPS as a new waypoint



# LAND NAVIGATION



## Communicating Location

If you are lost and can communicate with search personnel, try to give them the following info:

- General Location
- Type Of Navigation Grid Used
- Grid Location (Easting Then Northing)
  - Direction Of Travel If Moving

Note:

A 4/4 grid will put you within 10 meters. It is communicated by dropping the last digit in a 5-digit grid. For example, if your full 5-digit grid is 74356 / 63982, a 4/4 grid will be called out as  
7435 / 6398



# LAND NAVIGATION



## Declination

Magnetic Declination is the difference between True North (Longitude Line) and Magnetic North (where the compass needle points).


A compass needle ALWAYS points to Magnetic North.

Grid Declination is the difference between a Grid Reference Line and Magnetic North.






# LAND NAVIGATION



**Difference in True North  
And Magnetic North**




**Longitude Lines  
(True North)**



# LAND NAVIGATION

## Magnetic Declination



If you do not have a compass that adjusts for declination remember to add or subtract declination to your azimuth.



# LAND NAVIGATION








# LAND NAVIGATION

Depending on your map, it may be printed with True North Reference lines or Grid North Reference lines



True North  
(Longitude)

Grid  
North  
(UTM Or Other Grid)



# LAND NAVIGATION


## Adjusting For Declination For Map Use

Declination is the difference between true north and magnetic north when using the longitude lines as north reference.

Declination is the difference or spread between grid north and magnetic north when using the UTM grid lines as north reference.

If the MN line is left of the Reference Line you are using to measure your azimuth, then it will always be West Declination.  
If the MN line is right of the Reference Line it will always be East Declination


If you are using a compass that is not adjusted for declination, add the amount for west declination when going from map to real world, subtract the amount for east declination (when going from map to real world). If your compass is adjustable for declination, set it for the north reference declination value you are using. No further addition or subtraction is required.






# LAND NAVIGATION

## True North / Magnetic North / Grid North




If using Grid North as Reference then declination would be set to 6 degrees West  
If using True North as Reference then declination would be set to 3 degrees West







# LAND NAVIGATION



What is our declination value for each of the diagrams using Grid North Reference?



# LAND NAVIGATION



## 5-POINT LAND NAV CHECKLIST

1. Coordinates
2. Pace / Distance
3. Azimuth / Declination
4. Checkpoint / Terrain Association
5. Backstops, Handrails, etc.



# LAND NAVIGATION



## ADDITIONAL INFO

- **Determining Unknown Distance**
  - **Determining Height**






# LAND NAVIGATION

## DETERMINING UNKNOWN DISTANCE WITH COMPASS

Angle	tan(x)	Angle	tan(x)	Angle	tan(x)	Angle	tan(x)
0.0	0.00	25.0	.4663	40.0	1.0355	75.0	2.9642
1.0	.0175	26.0	.4877	41.0	1.0724	76.0	3.0777
2.0	.0349	27.0	.5095	42.0	1.1106	77.0	3.2799
3.0	.0524	28.0	.5317	43.0	1.1504	78.0	3.4654
4.0	.0699	29.0	.5543	44.0	1.1919	79.0	3.7321
5.0	.0875	30.0	.5773	45.0	1.2343	80.0	4.0108
6.0	.1051	31.0	.6009	46.0	1.2798	81.0	4.3315
7.0	.1228	32.0	.6248	47.0	1.3270	82.0	4.7046
8.0	.1405	33.0	.6494	48.0	1.3760	83.0	5.1408
9.0	.1584	34.0	.6746	49.0	1.4267	84.0	5.6713
10.0	.1763	35.0	.7005	50.0	1.4802	85.0	6.3158
11.0	.1944	36.0	.7269	51.0	1.5364	86.0	7.1154
12.0	.2126	37.0	.7538	52.0	1.6000	87.0	8.1443
13.0	.2309	38.0	.7813	53.0	1.6643	88.0	9.5144
14.0	.2493	39.0	.8098	54.0	1.7321	89.0	11.430
15.0	.2679	40.0	.8391	55.0	1.8044	90.0	14.301
16.0	.2867	41.0	.8693	56.0	1.8817	91.0	18.081
17.0	.3057	42.0	.9004	57.0	1.9643	92.0	23.036
18.0	.3248	43.0	.9325	58.0	2.0523	93.0	29.236
19.0	.3440	44.0	.9657	59.0	2.1460	94.0	37.816
20.0	.3634	45.0	1.0000	60.0	2.2460		
21.0	.3829			61.0	2.3526		
22.0	.4026			62.0	2.4671		
23.0	.4224			63.0	2.5891		
24.0	.4422			64.0	2.7191		



- 1) Shoot an azimuth from Point 1 to the object of unknown distance.
- 2) Turn 90 degrees from this azimuth and move to a second location (Point 2) that is a known distance from your first point (pace count 50 meters for example).
- 3) From Point 2 shoot another azimuth to the object of unknown distance.
- 4) Find the difference in degrees from these two azimuths (For example if your first azimuth was 10 degrees and your second azimuth was 340 degrees, then the difference is 30 degrees).
- 5) Subtract this difference from 90 (in the example above you would come up with 90-30=60)
- 6) Look on your tangent tables and find the tangent for the value (in the example, the value from the tangent tables for 60 is 1.732)
- 7) Multiply the distance you moved from Point 1 to Point 2 (50 meters) by the tangent of 1.732.
- 8)  $50 \times 1.732 = 86.6$  meters (distance from Point 1 to the object of unknown distance).

### EQUATION:

$$d = (\tan(90 - (A - B))) \times \text{Ref}$$

**d** = Distance (to be calculated)  
**Tan** = Tangent value of the resultant angle  
**A** = Greater value of the two measured bearing angles  
**B** = Lower value of the two measured bearing angles  
**Ref** = Measured reference distance between Point 1 & Point 2




# LAND NAVIGATION



## Using Basic Trigonometry To Determine Approximate Distance Across A River:

- 1) Mark a starting point along a straight stretch of the river as Point A.
- 2) Start at Point A and walk 5 paces (can be another number) along the side of the river to point B.
- 3) Turn 90 degrees and walk the same amount of paces to Point C.
- 4) Sight from Point C to Point A and find a distant point (D) on the other side of the river.
- 5) Return to Point A and count your paces until you are directly across from the point you sighted as D (this will be Point E).
- 6) The river is approximately the same distance in width as the distance you counted between Point A and E



This technique is handy if you need to know an approximate length of rope required to traverse a river, canyon, etc.



# LAND NAVIGATION



## Height Measurement Using An Inclinometer

### If angle is less than 45 degrees:

- Convert angle to percent of grade (see below).
- Multiply distance from object by percent of grade, then divide this by 100.
- Add eye (compass) level height to this value.

### Converting to percent of grade:

When an angle is less than 45 degrees you must convert angle to percent of grade. To do this multiply the angle tan value by 100. Example: if the angle is 35 degrees then the tan value is .7002, so  $.7002 \times 100 = 70.02$  (or rounded off to 70) percent grade.

Once you have percent of grade, to find height use this equation: Multiply the distance to the object by the percent of grade, and then divide this number by 100. For example: you are standing 30 feet away from a tree and your eye level is  $5 \frac{1}{2}$  feet. You measure an angle to the top of the tree as being 35 degrees. You convert this angle to percent of grade (70). So,  $30 \times 70 / 100 = 21$ . Add your eye level height back to this and the tree is 26.5 feet tall.

### If an angle is more than 45 degrees you can skip converting to percent of grade and use the tan value direct.

- Find Tan Value of angle.
- Multiply Tan value by distance away from object being measured.
- Add eye (compass) level height to this value.

For example if you are standing 30 feet away from a tree and your eye level is  $5 \frac{1}{2}$  feet. You measure an angle to the top of the tree as being 52 degrees. The tan value of 52 is 1.2799. So,  $(30 \times 1.2799) + 5.5 = 43.9$  feet tall.